

# SAFETY DATA SHEET

Creation Date 28-Apr-2009

Revision Date 29-Feb-2020

**Revision Number** 3

1. Identification			
Product Name	Acetone, HPLC Grade, 99.5+%		
Cat No. :	22928		
CAS-No Synonyms	67-64-1 2-Propanone		
Recommended Use Uses advised against Details of the supplier of the sa	Laboratory chemicals. Food, drug, pesticide or biocidal product use. fety data sheet		
Company Alfa Aesar Thermo Fisher Scientific Chemica 30 Bond Street Ward Hill, MA 01835-8099 Tel: 800-343-0660 Fax: 800-322-4757 Email: tech@alfa.com www.alfa.com	als, Inc.		
<b>Emergency Telephone Number</b> During normal business hours (M After normal business hours, call	onday-Friday, 8am-7pm EST), call (800) 343-0660.		

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Serious Eye Damage/Eye Irritation Specific target organ toxicity (single exposure) Target Organs - Central nervous system (CNS). Specific target organ toxicity - (repeated exposure) Target Organs - Kidney, Liver, spleen, Blood. Category 2 Category 2 Category 3

Category 2

### Label Elements

Signal Word Danger

### Hazard Statements

Highly flammable liquid and vapor

Causes serious eye irritation

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure



#### Precautionary Statements Prevention

Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge Wear protective gloves/protective clothing/eye protection/face protection Keep cool Response Get medical attention/advice if you feel unwell Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell Skin IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower Eves IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention Fire In case of fire: Use CO2, dry chemical, or foam for extinction Storage Store in a well-ventilated place. Keep container tightly closed Store locked up Disposal Dispose of contents/container to an approved waste disposal plant Hazards not otherwise classified (HNOC) Repeated exposure may cause skin dryness or cracking

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %	
Acetone	67-64-1	>95	

# 4. First-aid measures

General Advice	If symptoms persist, call a physician.
----------------	--

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Most important symptoms and effects Notes to Physician	. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema Treat symptomatically

# 5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point	-20 °C / -4 °F
Method -	CC (closed cup)
Autoignition Temperature	465 °C / 869 °F
Explosion Limits Upper Lower Oxidizing Properties	12.8 vol % 2.5 vol % Not oxidising
Sensitivity to Mechanical Impa	ct No information available

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

## Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

## Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Formaldehyde. Methanol.

## Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA_ Health 2	Flammability 3	<b>Instability</b> 0	Physical hazards N/A		
	6. Accidental re	lease measures			
Personal Precautions			dequate ventilation. Remove all		
Environmental Precautions	sources of ignition. Take precautionary measures against static discharges.nental PrecautionsShould not be released into the environment.				
Methods for Containment and CleanSoak up with inert absorbent material. Keep in suitable, closed containers for disposal.UpRemove all sources of ignition. Use spark-proof tools and explosion-proof equipment.					
	7. Handling	and storage			
Handling	Do not get in eyes, on skin	, or on clothing. Wear personal	protective equipment/face		

protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

### Storage

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

# 8. Exposure controls / personal protection

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Acetone	TWA: 250 ppm	(Vacated) TWA: 750 ppm	IDLH: 2500 ppm	TWA: 500 ppm
	STEL: 500 ppm	(Vacated) TWA: 1800 mg/m <sup>3</sup>	TWA: 250 ppm	STEL: 750 ppm
		(Vacated) STEL: 2400	TWA: 590 mg/m <sup>3</sup>	
		mg/m <sup>3</sup>	-	
		(Vacated) STEL: 1000 ppm		
		TWA: 1000 ppm		
		TWA: 2400 mg/m <sup>3</sup>		

#### <u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.
	9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	sweet
Odor Threshold	19.8 ppm
рН	7
Melting Point/Range	-95 °C / -139 °F
Boiling Point/Range	56 °C / 132.8 °F
Flash Point	-20 °C / -4 °F
Method -	CC (closed cup)
Evaporation Rate	5.6 (Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	12.8 vol %
Lower	2.5 vol %

Vapor Pressure	247 mbar @ 20 °C
Vapor Density	2.0
Specific Gravity	0.790
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	465 °C / 869 °F
Decomposition Temperature	> 4°C
Viscosity	0.32 mPa.s @ 20 °C
Molecular Formula	C3 H6 O
Molecular Weight	58.08
Refractive index	1.358 - 1.359

# 10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Heat, flames and sparks. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Strong reducing agents, Strong bases, Peroxides, Halogenated compounds, Alkali metals, Amines
Hazardous Decomposition Product	<b>s</b> Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> ), Formaldehyde, Methanol
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

# Product Information

Component Information	on					
Component		LD50 Oral		LD50 Dermal	LC50	Inhalation
Acetone		5800 mg/kg (Rat)	) > 15800 mg/kg (rabbit)		76 mg	ı/l, 4 h, (rat)
			>	7400 mg/kg (rat)		
<b>Toxicologically Syner</b>	gistic	Carbon tetrachlorie	de; Chloroform; Tr	chloroethylene; Bro	omodichlorometha	ne;
Products		Dibromochloromet	hane; N-nitrosodir	nethylamine; 1,1,2-	Trichloroethane; S	Styrene;
		Acetonitrile, 2,5-H	exanedione; Ethan	ol; 1,2-Dichloroben	zene	
Delayed and immedia	te effects as we	ell as chronic effe	cts from short an	d long-term expos	sure	
Irritation		Irritating to eyes				
Sensitization		No information available				
ochishization						
Carcinogenicity		The table below indicates whether each agency has listed any ingredient as a carcinogen.				
ea. ee gemeny						
Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico

	Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico			
	Acetone	67-64-1	Not listed	Not listed	Not listed	Not listed	Not listed			
Mutagenic Effects			No information available							
Reproductive Effects			No information available.							
Developmental Effects			No information available.							
Teratogenicity			No information available.							
STOT - single exposure			Central nervous system (CNS)							

STOT - repeated exposure	Kidney Liver spleen Blood
Aspiration hazard	No information available
Symptoms / effects,both acute and delayed	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated.

# 12. Ecological information

### Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	NOEC = 430 mg/l (algae; 96	Oncorhynchus mykiss: LC50	EC50 = 14500 mg/L/15 min	EC50 = 8800 mg/L/48h
	h)	= 5540 mg/l 96h	-	EC50 = 12700 mg/L/48
		Alburnus alburnus: LC50 =		EC50 = 12600 mg/L/48
		11000 mg/l 96h		-
		Leuciscus idus: LC50 =		
		11300 mg/L/48h		
		Salmo gairdneri: LC50 =		
		6100 mg/L/24h		

Persistence and Degradability

Persistence is unlikely based on information available.

# **Bioaccumulation/ Accumulation** No information available.

Mobility

Will likely be mobile in the environment due to its volatility.

Component		log Pow	
	Acetone	-0.24	
Other adverse effects	None known		

13. Disposal considerations						
Waste Disposal Methods	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.					

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acetone - 67-64-1	U002	-

14. Transport information					
DOT					
UN-No	UN1090				
Proper Shipping Name	ACETONE				
Hazard Class	3				
Packing Group	Ш				
TDG					
UN-No	UN1090				
Proper Shipping Name	ACETONE				
Hazard Class	3				
Packing Group	II				
ΙΑΤΑ					
UN-No	UN1090				
Proper Shipping Name	ACETONE				
Hazard Class	3				
Packing Group	ll				
IMDG/IMO					

UN-No Proper Shipping Name	UN1090 ACETONE
Hazard Class	3
Packing Group	II

# 15. Regulatory information

### United States of America Inventory

Component	CAS-No	TSCA	TSCA Inventory notification - Active/Inactive	TSCA - EPA Regulatory Flags
Acetone	67-64-1	Х	ACTIVE	-

### Legend:

TSCA - Toxic Substances Control Act, (40 CFR Part 710) X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

# International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Australia (AICS), China (IECSC), Korea (ECL).

Component	CAS-No	DSL	NDSL	EINECS	PICCS	ENCS	AICS	IECSC	KECL
Acetone	67-64-1	Х	-	200-662-2	Х	Х	Х	Х	KE-29367

### U.S. Federal Regulations

SARA 313	Not applicable
SARA 311/312 Hazard Categories	See section 2 for more information
CWA (Clean Water Act)	Not applicable
Clean Air Act	Not applicable
<b>OSHA</b> - Occupational Safety and Health Administration	Not applicable
CERCLA	This material, as supplied, contains one or more substances reg

gulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component		Hazardous Substances RQs	CERCLA EHS RQs	
Acetone		5000 lb	-	
California Proposition 65	This product does not contain any Proposition 65 chemicals.			

#### This product does not contain any Proposition 65 chemicals.

### U.S. State Right-to-Know

Regulations
-------------

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acetone	Х	Х	Х	-	Х

#### **U.S. Department of Transportation**

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

### **U.S. Department of Homeland** Security

This product does not contain any DHS chemicals.

### Other International Regulations

Mexico - Grade

Serious risk, Grade 3

	16. Other information
Prepared By	Health, Safety and Environmental Department Email: tech@alfa.com www.alfa.com
Creation Date Revision Date Print Date Revision Summary	28-Apr-2009 29-Feb-2020 29-Feb-2020 Initial Release.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# **End of SDS**