

SAFETY DATA SHEET

Version 6.0 Revision Date 09/18/2019 Print Date 10/04/2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifiers

Product name : Sodium hydroxide

Product Number : S8045 Brand SIGALD

Index-No. : 011-002-00-6 : 1310-73-2 CAS-No.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company Sigma-Aldrich Inc.

> 3050 Spruce Street ST. LOUIS MO 63103

UNITED STATES

Telephone : +1 314 771-5765 : +1 800 325-5052 Fax

Emergency telephone number

Emergency Phone # : +1-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Corrosive to metals (Category 1), H290 Skin corrosion (Category 1A), H314

Serious eye damage (Category 1), H318

Short-term (acute) aquatic hazard (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H290 May be corrosive to metals.

SIGALD - S8045 Page 1 of 10



H314 H402	Causes severe skin burns and eye damage. Harmful to aquatic life.
Precautionary statement(s)	
P234	Keep only in original container.
P260	Do not breathe dust or mist.
P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 +	IF IN EYES: Rinse cautiously with water for several minutes.
P310	Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner liner.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Caustic soda

Formula : NaOH
Molecular weight : 40.00 g/mol
CAS-No. : 1310-73-2
EC-No. : 215-185-5
Index-No. : 011-002-00-6

Component	Classification	Concentration
Sodium hydroxide		
	Met. Corr. 1; Skin Corr. 1A; Eye Irrit. 2A; Aquatic Acute 3; H290, H314, H319, H402 Concentration limits: 0.5 - < 2 %: Skin Irrit. 2, H315; 0.5 - < 2 %: Eye Irrit. 2, H319; >= 5 %: Skin Corr. 1A, H314; 2 - < 5 %: Skin Corr. 1B, H314; >= 1 %: Met. Corr. 1, H290;	<= 100 %

SIGALD - S8045 Page 2 of 10



SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Sodium oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

SIGALD - S8045 Page 3 of 10



6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Storage class (TRGS 510): 8B: Non-combustible, corrosive hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Sodium hydroxide	1310-73-2	С	2 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Upper Respiratory Tract irritation Eye irritation Skin irritation		
		С	2 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	2 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		С	2 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

Derived No Effect Level (DNEL)

Derived No Litect Level (DNLL)						
Application Area	Exposure routes	Health effect	Value			
Workers	Inhalation	Long-term local effects	1 mg/m3			

SIGALD - S8045 Page 4 of 10



| Consumers | Inhalation | Long-term local effects | 1 mg/m3

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SIGALD - S8045 Page 5 of 10



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: pellets Colour: white

b) Odour odourless

c) Odour Threshold No data available

d) pH 14 at 50 g/l at 20 °C (68 °F)

e) Melting Melting point/range: 318 °C (604 °F) point/freezing point

f) Initial boiling point and boiling range

nitial boiling point 1,390 °C 2,534 °F

g) Flash point ()Not applicableh) Evaporation rate No data availablei) Flammability (solid, No data available

gas)

No data available

j) Upper/lower flammability or explosive limits

k) Vapour pressure < 24.00 hPa at 20 °C (68 °F)

4.00 hPa at 37 °C(99 °F)

I) Vapour density 1.38 - (Air = 1.0)m) Relative density 2.1300 g/cm3

n) Water solubility ca.1,260 g/l at 20 °C (68 °F)

o) Partition coefficient: No data available

n-octanol/water

p) Auto-ignition I

No data available

temperature q) Decomposition

No data available

temperature
r) Viscosity No data available

No data available

t) Oxidizing properties No data available

9.2 Other safety information

s) Explosive properties

Bulk density ca.1,150 kg/m3

Relative vapour

density

1.38 - (Air = 1.0)

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

SIGALD - S8045 Page 6 of 10

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents, Strong acids, Organic materials

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Sodium oxides Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: Corrosive to respiratory system.

Dermal: No data available

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Severe skin irritation - 24 h

Remarks: (RTECS)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

(OECD Test Guideline 405) Causes serious eye damage.

Respiratory or skin sensitisation

Patch test: - Human Result: negative Remarks: (ECHA)

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Acute oral toxicity - If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

Acute inhalation toxicity - burns of mucous membranes, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: WB4900000

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC50 - Gambusia affinis (Mosquito fish) - 125 mg/l - 96 h

Remarks: (ECOTOX Database)

Toxicity to daphnia and other aquatic

EC50 - Ceriodaphnia (water flea) - 40.4 mg/l - 48 h Remarks: (ECHA)

invertebrates

EC50 - Photobacterium phosphoreum - 22 mg/l - 15 min Toxicity to bacteria

Remarks: (External MSDS)

12.2 Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Neutralisation possible in waste water treatment plants.

Discharge into the environment must be avoided.

SIGALD - S8045 Page 8 of 10

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 1823 Class: 8 Packing group: II

Proper shipping name: Sodium hydroxide, solid

Reportable Quantity (RQ): 1000 lbs Poison Inhalation Hazard: No

IMDG

UN number: 1823 Class: 8 Packing group: II EMS-No: F-A, S-B

Proper shipping name: SODIUM HYDROXIDE, SOLID

IATA

UN number: 1823 Class: 8 Packing group: II

Proper shipping name: Sodium hydroxide, solid

SECTION 15: Regulatory information

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

No SARA Hazards

Massachusetts Right To Know Components

Sodium hydroxide CAS-No. Revision Date 1310-73-2 1989-08-11

Pennsylvania Right To Know Components

Sodium hydroxide CAS-No. Revision Date 1310-73-2 1989-08-11

New Jersey Right To Know Components

Sodium hydroxide CAS-No. Revision Date 1310-73-2 1989-08-11

SIGALD - S8045 Page 9 of 10



California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Further information

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.0 Revision Date: 09/18/2019 Print Date: 10/04/2019

SIGALD - S8045 Page 10 of 10

