# **SAFETY DATA SHEET**

Version 6.0 Revision Date 01/31/2017 Print Date 08/08/2019

## 1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Isopropyl alcohol

Product Number : I9030 Brand : SIGALD Index-No. : 603-117-00-0

CAS-No. : 67-63-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

## 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

## GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

SIGALD- 19030 Page 1 of 10

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P242 Use only non-sparking tools. Take precautionary measures against static discharge. P243 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P261 Wash skin thoroughly after handling. P264 Use only outdoors or in a well-ventilated area. P271 Wear protective gloves/ eye protection/ face protection. P280 IF ON SKIN (or hair): Take off immediately all contaminated clothing. P303 + P361 + P353 Rinse skin with water/shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. P337 + P313 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to Store in a well-ventilated place. Keep container tightly closed. P403 + P233 Store in a well-ventilated place. Keep cool. P403 + P235 P405 Store locked up. P501 Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 Substances

Synonyms : 2-Propanol

<l>>sec</>-Propyl alcohol

Isopropyl alcohol Isopropanol

Formula : C<SB>3</>H<SB>8</>O

Molecular weight : 60.10 g/mol CAS-No. : 67-63-0 EC-No. : 200-661-7 Index-No. : 603-117-00-0

**Hazardous components** 

| Component  | Classification   | Concentration |
|------------|--|---------------|
| 2-Propanol |  |               |
|            | Flam. Liq. 2; Eye Irrit. 2A;<br>STOT SE 3; H225, H319,<br>H336 | <= 100 %      |

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 4. FIRST AID MEASURES

## 4.1 Description of first aid measures

## **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

## In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

SIGALD- 19030 Page 2 of 10

## In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

## 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

## 4.3 Indication of any immediate medical attention and special treatment needed

No data available

## 5. FIREFIGHTING MEASURES

## 5.1 Extinguishing media

## Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

## 5.2 Special hazards arising from the substance or mixture

Carbon oxides

## 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

## 6. ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

## 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

## 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Flash back possible over considerable distance. Container explosion may occur under fire conditions. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

Handle under nitrogen, protect from moisture. Store under nitrogen. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Handle and store under inert gas. Hygroscopic.

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SIGALD- 19030 Page 3 of 10

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters

Components with workplace control parameters

| Component  | CAS-No. | Value  | Control                | Basis   |
|------------|---------|--|------------------------|---|
|            |         |  | parameters             |   |
| 2-Propanol | 67-63-0 | TWA  | 200.000000<br>ppm      | USA. ACGIH Threshold Limit Values (TLV)                             |
|            | Remarks | Central Nerv   | vous System impai      | irment  |
|            |         |  | iratory Tract irritati |   |
|            |         | Eye irritation   |                        |   |
|            |         | Substances for which there is a Biological Exposure Index or Indices (see BEI® section)  |                        |   |
|            |         |  | ble as a human ca      | arcinogen   |
|            |         | TWA  | 200 ppm                | USA. ACGIH Threshold Limit Values (TLV)                             |
|            |         | Central Nerv   | vous System impai      | irment  |
|            |         | Upper Respiratory Tract irritation  Eye irritation   |                        |   |
|            |         | •  |                        | a Biological Exposure Index or Indices                              |
|            |         | (see BEI® s  | ection)                |   |
|            |         | Not classifia  | ble as a human ca      | arcinogen   |
|            |         | STEL   | 400.000000             | USA. ACGIH Threshold Limit Values                                   |
|            |         |  | ppm                    | (TLV)   |
|            |         | Central Nerv   | vous System impai      | irment  |
|            |         |  | iratory Tract irritati | on  |
|            |         | Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section)   |                        |   |
|            |         |  |                        |   |
|            |         |  |                        |   |
|            |         |  | ble as a human ca      |   |
|            |         | STEL   | 400 ppm                | USA. ACGIH Threshold Limit Values (TLV)                             |
|            |         | Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen |                        |   |
|            |         |  |                        |   |
|            |         |  |                        |   |
|            |         |  |                        |   |
|            |         |  |                        |   |
|            |         |  |                        |   |
|            |         | TWA  | 400.000000             | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air |
|            |         |  | ppm<br>980.000000      | Contaminants  |
|            |         |  | mg/m3                  | Contaminants  |
|            |         | The value in mg/m3 is approximate.  TWA 400.000000 USA. NIOSH Recommend  |                        |   |
|            |         |  |                        |   |
|            |         |  | ppm                    | Exposure Limits   |
|            |         |  | 980.000000             | 1 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3                             |
|            |         |  | mg/m3                  |   |
|            |         | ST   | 500.000000             | USA. NIOSH Recommended  |
|            |         |  | ppm                    | Exposure Limits   |
|            | I       |  | 1,225.000000           |   |
|            |         |  | mg/m3                  |   |

**Biological occupational exposure limits** 

| biological occupational exposure illilits |         |            |         |            |                    |
|---|---------|------------|---------|------------|--------------------|
| Component                                 | CAS-No. | Parameters | Value   | Biological | Basis              |
|   |         |            |         | specimen   |                    |
| 2-Propanol                                | 67-63-0 | Acetone    | 40.0000 | Urine      | ACGIH - Biological |
|   |         |            | mg/l    |            | Exposure Indices   |
|   |         |            |         |            | (BEI)              |

SIGALD- 19030 Page 4 of 10

|  |   |      | Remarks        | End of shift at end of workweek |
|--|---|------|----------------|---------------------------------|
|  | • | <br> | <br>. (5):=: ) |                                 |

## **Derived No Effect Level (DNEL)**

| Application Area | Exposure routes | Health effect              | Value         |
|------------------|-----------------|----------------------------|---------------|
| Workers          | Inhalation      | Long-term systemic effects | 500 mg/m3     |
| Workers          | Skin contact    | Long-term systemic effects | 888mg/kg BW/d |
| Consumers        | Inhalation      | Long-term systemic effects | 89 mg/m3      |
| Consumers        | Skin contact    | Long-term systemic effects | 319mg/kg BW/d |
| Consumers        | Ingestion       | Long-term systemic effects | 26mg/kg BW/d  |

## **Predicted No Effect Concentration (PNEC)**

| Compartment          | Value      |
|----------------------|------------|
| Soil                 | 28 mg/kg   |
| Marine water         | 140.9 mg/l |
| Fresh water          | 140.9 mg/l |
| Marine sediment      | 552 mg/kg  |
| Fresh water sediment | 552 mg/kg  |

## 8.2 Exposure controls

## **Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

## Personal protective equipment

## Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

## Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

### Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 480 min

Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm Break through time: 60 min

Material tested:Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

## **Body Protection**

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use (US) or type ABEK (EN 14387) respirator cartridges as a backup to enginee protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (FU)

## Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SIGALD- 19030 Page 5 of 10

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

Form: liquid **Appearance** 

Colour: colourless

b) Odour alcohol-like

Odour Threshold No data available d) рΗ No data available

Melting point/freezing

point

Melting point/range: -89.5 °C (-129.1 °F) - lit.

Initial boiling point and

boiling range

82 °C (180 °F) - lit.

Flash point 12.0 °C (53.6 °F) - closed cup

3.0 h) Evaporation rate

No data available Flammability (solid, gas)

Upper/lower flammability or explosive limits Upper explosion limit: 12.7 %(V) Lower explosion limit: 2 %(V)

Vapour pressure 43.2 hPa at 20.0 °C (68.0 °F) k)

58.7 hPa at 25.0 °C(77.0 °F)

No data available I) Vapour density

m) Relative density 0.785 g/cm3 at 25 °C (77 °F)

Water solubility completely soluble Partition coefficient: nlog Pow: 0.05

octanol/water

p) Auto-ignition 425.0 °C (797.0 °F)

temperature

Decomposition

temperature

No data available

No data available r) Viscosity Explosive properties No data available s) No data available Oxidizing properties

9.2 Other safety information

> Surface tension 20.8 mN/m at 25.0 °C (77.0 °F)

## **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

No data available

## 10.2 Chemical stability

May form peroxides of unknown stability.

Test for peroxide formation before distillation or evaporation. Test for peroxide formation or discard after 1 year.

Stable under recommended storage conditions.

Stable under recommended storage conditions.

#### Possibility of hazardous reactions 10.3

Vapours may form explosive mixture with air. Vapours may form explosive mixture with air.

SIGALD- 19030 Page 6 of 10

## 10.4 Conditions to avoid

Heat, flames and sparks.

## Incompatible materials

Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids

#### Hazardous decomposition products 10.6

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

## 11. TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects

## **Acute toxicity**

LD50 Oral - Rat - 5,045 mg/kg(2-Propanol)

Remarks: Behavioral: Altered sleep time (including change in righting reflex). Behavioral: Somnolence (general depressed activity).

LC50 Inhalation - Rat - 8 h - 16000 ppm(2-Propanol)

LD50 Dermal - Rabbit - 12,800 mg/kg(2-Propanol)

No data available(2-Propanol)

## Skin corrosion/irritation

Skin - Rabbit(2-Propanol)

Result: Mild skin irritation

## Serious eye damage/eye irritation

Eyes - Rabbit(2-Propanol) Result: Eye irritation - 24 h

## Respiratory or skin sensitisation

No data available(2-Propanol)

## Germ cell mutagenicity

No data available(2-Propanol)

#### Carcinogenicity

This product is or contains a component that is not classifiable as to its classification. (2-Propanol) (2-Propanol)

(2-Propanol)

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

#### Reproductive toxicity

No data available(2-Propanol)

No data available(2-Propanol)

#### Specific target organ toxicity - single exposure

Inhalation, Oral - May cause drowsiness or dizziness.(2-Propanol)

## Specific target organ toxicity - repeated exposure

No data available

#### Aspiration hazard

No data available(2-Propanol)

SIGALD- 19030 Page 7 of 10

#### **Additional Information**

RTECS: NT8050000

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects., Aspiration may lead to:, Lung oedema, Pneumonia(2-Propanol)

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(2-Propanol)

Kidney - Irregularities - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence(2-Propanol)

## 12. ECOLOGICAL INFORMATION

## 12.1 Toxicity

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 9,640.00 mg/l - 96 h(2-

Propanol)

Toxicity to daphnia and

other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 5,102.00 mg/l - 24 h(2-Propanol)

Immobilization EC50 - Daphnia magna (Water flea) - 6,851 mg/l - 24 h(2-

Propanol)

Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - > 2,000.00 mg/l - 72 h(2-

Propanol)

EC50 - Algae - > 1,000.00 mg/l - 24 h(2-Propanol)

## 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No bioaccumulation is to be expected (log Pow <= 4).

## 12.4 Mobility in soil

No data available(2-Propanol)

## 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

No data available

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

## **Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

## Contaminated packaging

Dispose of as unused product.

## 14. TRANSPORT INFORMATION

DOT (US)

UN number: 1219 Class: 3 Packing group: II

Proper shipping name: Isopropanol Poison Inhalation Hazard: No

**IMDG** 

UN number: 1219 Class: 3 Packing group: II EMS-No: F-E, S-D

SIGALD- 19030 Page 8 of 10

Proper shipping name: ISOPROPANOL

**IATA** 

UN number: 1219 Class: 3 Packing group: II

Proper shipping name: Isopropanol

## 15. REGULATORY INFORMATION

## **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

## **SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date 67-63-0 1987-01-01

SARA 311/312 Hazards

2-Propanol

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**Massachusetts Right To Know Components** 

2-Propanol CAS-No. Revision Date 67-63-0 1987-01-01

**Pennsylvania Right To Know Components** 

CAS-No. Revision Date

2-Propanol 67-63-0 1987-01-01

**New Jersey Right To Know Components** 

2-Propanol CAS-No. Revision Date 67-63-0 1987-01-01

## California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## 16. OTHER INFORMATION

## Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

## **HMIS Rating**

Health hazard: 2
Chronic Health Hazard: \*
Flammability: 3
Physical Hazard 0

**NFPA** Rating

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

## **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

SIGALD- 19030 Page 9 of 10

## **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 6.0 Revision Date: 01/31/2017 Print Date: 08/08/2019

SIGALD- 19030 Page 10 of 10